



The Amega range of Instruments

Smart white and red graphics on a black dial background, these very low profile bezels follow the curve of the lense to eliminate water trapping. Design with domed glass sheds water and resists scratching.

Key Features

- Perimeter & through-dial lighting is provided for excellent night visibility
- Very low profile bezels
- Convex, domed glass lenses are scratch resistant
- White and red graphics on a black background
- Pointers are white with a black hub
- Shielded to prevent magnetic interference
- Silicone dampening eliminates pointer bounce



For Sender information refer to the Teleflex Sender Code data sheet or visit the Teleflex website at www.tfx.com

Actual hole sizes: Nominal 2"=2.13/2.16" except Hourmeter =2.00/2.06". Nominal 3"=3.41/3.44".

Request Dimension data sheet for complete dimension data.

For full ordering see page 2

contact us for more details:
e-mail: intmarine@teleflex.com
www.teleflexmarine-int.com

Teleflex Marine International Sales & Marketing
Gaunts Business Centre,
Gaunts Common,
Wimborne,
Dorset BH21 4JT
England

Ordering Information	Resistance Range	Sender Code	Part No.
Ammeter, 60-0-60	NA	N/R	59310E
Fuel gauge (E-F)	240-33ohm	F	57902E
Hourmeter 10,000 hrs	NA	N/R	58154E
Eng Oil Pressure gauge 0-80 PSI	240-33ohm	C	57903E
Eng Oil Pressure gauge 0-100 PSI	240-33ohm	C	57929E
Eng Oil Pressure gauge 5 bar	10-180ohm	VDO type	62155E
Eng Oil Pressure gauge 10 bar	10-180ohm	VDO type	62156E
O/B Water Pres Kit 0-30 PSI	NA	WP(included)	59630E
O/B Water Pres Kit 0-15 PSI	NA	WP(included)	58392E
Speedo Kit 0-35mph (inc Pitot and Hose)	NA	G (included)	58342E
Speedo Kit 0-50mph (inc Pitot and Hose)	NA	G (included)	57898E
Speedo Kit 0-65mph (inc Pitot and Hose)	NA	G (included)	57900E
Speedo Kit 40 Knot (inc Pitot and Hose)	NA	G (included)	62157E
Speedo Kit 75 Knot (inc Pitot and Hose)	NA	G (included)	62158E
Speedo Head Only 0-35mph	NA	Requires G or Eng.Mfr	63032E
Speedo Head Only 0-50mph	NA	Requires G or Eng.Mfr	63033E
Speedo Head Only 0-65mph	NA	Requires G or Eng.Mfr	63034E
Speedo Head Only 40 Knot	NA	Requires G or Eng.Mfr	63035E
Speedo Head Only 75 Knot	NA	Requires G or Eng.Mfr	63036E
Tachometer, 0-4000 RPM Diesel Alt	NA	Alternator	58136E
Tachometer, 0-7000 RPM	NA	O/B Alt or Coil	58255E
I/O Water Temp Gauge 120-240 F	240ohm@120F	D	57904E
I/O Water Temp Gauge 40-120 C	22ohms-450ohms	VDO type	62159E
Trim, Evinrude/Johnson O/B's, Suzuki 4-stroke 02 & on	UP 1 OHM, Down 88 OHM	Eng Mfr supply	58431E
Trim, Mariner/Merc, Yamaha 2001 & on	UP 167 OHM, Down 10 OHM	Eng Mfr supply	57905E
Trim, Yamaha Outboards, pre 2001	UP 411 OHM, Down 110 OHM	Eng Mfr supply	61748E
Voltmeter, 8-18 Volts	NA	N/R	57901E
Voltmeter, 20-32 Volts	NA	N/R	64279E
Quartz Clock	quartz analogue	N/R	58861E